

## CFZ-DT-200 Edition

CFZ-DT-200 high-end edition and professional strong plastic structured models with axial fan, which need to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



### APPLICATIONS:



Factories



Workshops



Entertainment Centers



Supermarkets & Malls



Prayer Halls & Schools

### SPECIFICATIONS



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Engineering Plastic



#### Model

#### CFZ-DT-200B

#### CFZ-DT-200S

#### CFZ-DT-200T

Discharge Type

Bottom

Side

Top

Voltage/Frequency

220~240V/380~415V

220~240V/380~415V

220~240V/380~415V

Frequency

50~60 Hz

50~60 Hz

50~60 Hz

Max. Air Flow

20,000 m<sup>3</sup>/h

20,000 m<sup>3</sup>/h

20,000 m<sup>3</sup>/h

Working Current

4.8A/2.7A

4.8A/2.7A

4.8A/2.7A

Power Consumption

1.1 KW

1.1 KW

1.1 KW

Dimensions

1120\*1120\*1050mm

1120\*1120\*1050mm

1120\*1120\*1050mm

Air Outlet Size

670\*670 mm

670\*670 mm

730\*730 mm

Net Weight

60 Kg

60 Kg

60 Kg

Water Tank Capacity

25 L

35 L

35 L

Water Consumption

65 L/h

65 L/h

65 L/h

### DUCTED SERIES