

CFZ-DT-300 Edition

CFZ-DT-300 Edition are popular stainless steel structured model, the chassis and top cover are made of stainless steel, and the pillars are made of Aluminum alloy, with powder coating surface treatment, robust and reliable.

Axial-flow ventilation unit providing large airflow, which need to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



APPLICATIONS:

-  Factories
-  Workshops
-  Entertainment Centers
-  Supermarkets & Malls
-  Prayer Halls & Schools



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Engineering Plastic



SPECIFICATIONS

Model	CFZ-DT-300B	CFZ-DT-300S
Discharge Type	Bottom	Side
Voltage/Frequency	380~415V/50~60 Hz	380~415V/50~60 Hz
Max. Air Flow	30,000 m ³ /h	30,000 m ³ /h
Working Current	5.6A	5.6A
Power Consumption	2.2 KW	2.2 KW
Dimensions	1500*1500*1350 mm	1500*1580*1350 mm
Air Outlet Size	800*800 mm	800*800 mm
Net Weight	170 Kg	180 Kg
Water Tank Capacity	65 L	65 L
Water Consumption	117 L/h	117 L/h

DUCTED SERIES