

CFZ-DT-350 Edition

CFZ-DT-350 high-end edition and professional strong plastic structured models with axial fan, which need to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



Self Cleaning Function



Digital Control Panel



100% Copper Wired Motor



UV Stabilized Plastic Body



APPLICATIONS:



Workshops



Prayer Halls & Schools



Factories



Supermarkets & Malls

SPECIFICATIONS

| Model | CFZ-DT-350B | CFZ-DT-350T |
|---------------------------|--------------------------|--------------------------|
| Discharge Type | Bottom | Top |
| Voltage/Frequency/Phase | 380V/50Hz/3Ph | 380V/50Hz/3Ph |
| Speed | Single Speed | Single Speed |
| Max. Air Flow | 35,000 m ³ /h | 35,000 m ³ /h |
| Working Current | 11.2 A/6.3 A | 11.2 A/6.3 A |
| Power Consumption | 3.0 kW | 3.0 kW |
| Dimensions | 1350x1350x1350 mm | 1350x1350x1370 mm |
| Air Outlet Size | 800x800 mm | 800x800 mm |
| Water Tank Capacity | 40 L | 40 L |
| Evaporation Capacity | 142 L/h | 142 L/h |
| Net Weight | 118 Kg | 128 Kg |
| Applicable Area | 250~350 m ² | 250~350 m ² |
| Max. Air Pressure | 330 Pa | 330 Pa |
| Noise | <=74 | <=74 |
| Evaporative Efficiency | 88 % | 88 % |
| Run Weight | 190 kg | 200kg |
| Sensible Cooling Capacity | 98 kW | 98 kW |
| Energy Efficiency Ratio | 33 kW/kW | 33 kW/kW |

DUCTED SERIES

