

CFZ-DT-360 Edition

CFZ-DT-360 Edition are popular stainless steel structured model, the chassis and top cover are made of stainless steel, the pillars are made of Aluminum alloy, with powder coating surface treatment, robust and reliable. Axial-flow ventilation unit provides large airflow, which needs to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



APPLICATIONS:

-  Factories
-  Workshops
-  Entertainment Centers
-  Supermarkets & Malls
-  Prayer Halls & Schools



Fully Automated Function



Self Cleaning Function



Reverse Air Supply Function



Digital Control Panel



100% Copper Wired Motor



SS201 Body



SPECIFICATIONS

Model

Discharge Type

Voltage/Frequency

Max. Air Flow

Working Current

Power Consumption

Dimensions

Air Outlet Size

Net Weight

Water Tank Capacity

Water Consumption

CFZ-DT-360B

Bottom

380~415V/50~60 Hz

36,000 m³/h

6.5 A

3.0 KW

1500*1500*1350mm

800*800 mm

175 Kg

65 L

150 L/h

CFZ-DT-360S

Side

380~415V/50~60 Hz

36,000 m³/h

6.5 A

3.0 KW

1500*1580*1350mm

800*800 mm

185 Kg

65 L

150 L/h

DUCTED SERIES