

CFZ-DT-C Edition

CFZ-DT-C Edition are popular stainless steel structured model, metal housing and powder coating surface treatment, robust and reliable. Centrifugal-type ventilation unit provides high hydrostatic pressure and long-distance fresh air delivery. Which needs to be installed with air ducting system. Fixed installation model is designed to be installed on solid places such as outside wall, grounds, concrete or Zinc-steel structured roof.



APPLICATIONS:

-  Factories
-  Workshops
-  Entertainment Centers
-  Supermarkets & Malls
-  Prayer Halls & Schools

SPECIFICATIONS

-  Fully Automated Function
-  Self Cleaning Function
-  Digital Control Panel
-  100% Copper Wired Motor
-  SS201 Body

Model	CFZ-DT-C250	CFZ-DT-C350	CFZ-DT-C450	CFZ-DT-C600
Type	Centrifugal	Centrifugal	Centrifugal	Centrifugal
Voltage/Frequency	380~415V/50~60 Hz	380~415V/50~60 Hz	380~415V/50~60 Hz	380~415V/50~60 Hz
Max. Air Flow	25,000 m ³ /h	35,000 m ³ /h	45,000 m ³ /h	60,000 m ³ /h
Working Current	11.6 A	15.4 A	24.5 A	30.3 A
Power Consumption	5.5 KW	7.5 KW	11 KW	15.5 KW
Dimensions	1500*1580*1400mm	1770*1770*1440mm	2090*1970*1700mm	2090*1970*1700mm
Air Outlet Size	620*570mm	782*700mm	862*700mm	926*834mm
Net Weight	300 Kg	450 Kg	585 Kg	650 Kg
Water Tank Capacity	65 L	80 L	100 L	100 L
Water Consumption	117L/h	220L/h	260L/h	380L/h



DUCTED SERIES